



DYNAMO ULTRA[®] ALL-IN-ONE CETANE BOOSTER

DU-AIO-CB

Product Data Sheet

Performance Technology

Multifunctional High-Performance Diesel Fuel Treatment Additive

DYNAMO ULTRA[®] All-In-One Cetane Booster is a High-Performance Multifunctional Diesel Fuel Additive that Greatly Increases Fuel Economy [**Avg 26.98% | National AVG via Independent Testing**], Restores & Improves Torque & Power, Cleans and Maintains Pumps & Injectors, (including newer model year engines Operating High Pressure Common Rail Injectors), Reduces Carbon Residue & Sulfur, Prevents Sludging, Improves Lubricity, and, via Catalyst and Atomizing Agents, Increases Thermal Efficiency Burn.

For Use In:

- Large Trucks / Semi Tractors
- Generators
- Mining Equipment
- Marine Engines (Marine Cetane B)
- Construction Equipment
- Military & Emergency Vehicles
- Railroad Locomotive Engines
- Buses
- Farm Equipment
- Passenger Vehicles
- Boats of all sizes (Marine Cetane Booster)

Application

At Recommended Treat Rate of 640:1, DYNAMO ULTRA[®] AIO Cetane Booster provides the following Performance Improving Benefits:

- GREATLY Improves Fuel Economy.
- Increases Cetane Number: up to 5-points.
- Increased Thermal Efficiency Burn.
- Restores & Improves Torque & Power.
- Cleans and Prevents Up To 100% of ALL Injector Fouling Deposits
- Provides Superior Wear Protection for Pumps and Injectors.
- Reduces Maintenance Cost & Downtime
- Improves Cold-Flow & cold weather starting.
- Reduces Engine Noise – Smoother Idle.
- Reduces Exhaust Emissions, (THC, CO, NOx, CO2, PM). [~ 23% PM Reduction]
- Reduces Carbon Residue & Sulfur Content in Diesel Fuel, thereby Reducing Output of Carbon, Soot & Ash, Reducing DPF Issues & Regens, thereby Reducing DEF Consumption.
- Fuel Stabilizers Inhibit Gum Formation and Provide Thermal and Oxidative Stability, Lubricity, Corrosion Protection and Water Dispersancy. Increased Induction Period!
- Corrosion Inhibitors & Lubricity Improvers Work on a Molecular Level with Surface Active Chemistry & Long-Chain Molecules, Approved Under Military Specifications.

Additional Information

DYNAMO ULTRA[®] AIO Cetane Booster may be Continuously, or Batch Blended into Diesel Fuel.

Dosing Systems

CyberFuels[™] Inc. offers both Tank Farm / Bulk Storage Injection Couplers and Tractor, Onboard Dosing Systems.

Material Compatibility

DYNAMO ULTRA[®] AIO Cetane Booster is Compatible with Engine & Fuel Systems' Materials Of Construction when Dosed at the Recommended Treat Rate of 640:1. CyberFuels[™] Has Treated More Than 65M Gallons of Fuel with NO Adverse Issues.

EPA Registration

NO. 273620002
40CFR80.591 Compliant
LEGAL DIESEL Fuel Additive

Typical Properties

Appearance.....	Clear Amber Liquid
Physical State.....	Liquid
Density, lbs./gal 65°F (18.3°C).....	6.82
pH.....	8.4
Pour Point, °F (°C).....	<-40 (<-86)
Flash Point, °F (°C).....	~23 (~-5)
Recommended Treat Rate.....	640:1 [1,562.5 ppm]

